

**IT JUST OUTMANEUVERED THE REST.
AGAIN.**



SWEFOG ULTIMATE 2000 DMX.

THE EVOLUTION OF PERFECTION

SWEFOG
Technology Group AB

The best atmospheric hazer ever to wear the Swefog logo is the product of two decades of fogmaking and a ground-up engineering effort.

Zealous attention to detail is what separates Swefog products from the mainstream. Professional-grade design and engineering means a commitment to a higher standard. In place of flashy doodads and gimmicks, Swefog hazers are endowed with innovation and technology that uplifts everyday use.

Again, Swefog sets a reference standard with the Ultimate 2000 DMX, the 4th generation of atmospheric hazers.

No other haze – water, glycerine or glycol-based – compares to the haze of Ultimate 2000 DMX.

The haze is virtually invisible until it is illuminated, and it enhances the beams from projected lights without loss of light illumination power.

Unbeaten reliability, performance and value for money, the 4th generation Ultimate hazers represents a true industry standard that other hazers compares to.

Proudly hand-made in Sweden.

HIGHLIGHTS:

- Instant ON, NO warm-up time, NO heat, NO glycols, NO water, NO spirits.
- Fully integrated DMX control, uses one channel only.
- Manual or DMX control mode. Illuminated LED display, auto-store of DMX channel at power-off, perfect for touring use.
- Extremely low fluid consumption, 0.05 ltr (0.01 us gal) per hour at continuous operation & full output. A 5L (1.3 U.S. gal) fluid canister will last for approximate 80 (!) hours of continuous operation at full output.
- An advanced internal 5 micron filter system ensures the safest, cleanest atmospheric haze. □
- Features a new air filter system; in & outlets are protected with an easily interchangeable filter material, keeping internal parts clean.
- New, ergonomic AluGrip handle and a perfect balanced design makes Ultimate 2000 fully portable.

Available in 240V 50 Hz (CE) and 115V 60 Hz versions.

DIMS & WEIGHT, NET:

LxWxH: 383 x 204 x 388 mm / 19.3 kgs
LxWxH: 15.1" x 8.0" x 15.3" / 42.5 lbs

DIMS & WEIGHT, BOXED:

LxWxH: 471 x 300 x 485 mm / 20.1 kgs
LxWxH: 18.5" x 11.8" x 19.1" / 44.3 lbs

The design of Swefog Ultimate 2000 DMX is a registered community design and copy protected by EU & international laws. The Swefog & Swefog Ultimate brand names & logotypes are registered trademarks.



Ultimate 2000DMX comes fully loaded with integrated DMX 512 as a standard feature.



The reference standard that other hazers compares to: The Swefog Ultimate 2000 DMX.

SWEFOG

Technology Group AB

ULTIMATE 300

THE ULTIMATE 300 IS A HIGH OUTPUT CRACKER HAZER.

THE COMPRESSOR AND HAZE UNITS ARE ABLE TO SEPERATE FOR THE ULTIMATE IN QUIET OPERATION.

THE HAZER FEATURES THE "WHISPER" TECHNOLOGY. FAN NOISE IS REDUCED, AND IT OPERATES VIRTUALLY SILENT.

AVAILABLE WITH INTEGRATED DMX INTERFACE (optional).

Common features:

- Instant on, no warm-up time. Continuous operation.
- Air compressor operation. No heat, no water, no glycol.
- Extremely low fluid consumption - 40+ hours runtime, 3+ hours hangtime.
- Integrated DMX control available as an option. Uses one channel only. Decimal-type (no binary) rotary address switches for quick and easy addressing.
- Industry standard quick-lock metal tube fittings. 0,5 & 10 m extension tubes supplied.
- Quick & safe lock / unlock operation, with the use of mini butterfly catches.

Haze unit features:

- New Swefog V-tec type B 3-way high output fluid vapor splitters.
- Swefog "whisper" technology reduces fan noise during operation, and the hazer operates virtually silent.
- Swefog EC EasyClean™ nozzle / filter unit, and industrial super-rapid internal tube fittings allowing for quick and easy cleaning without the need of special tools.
- Hydro-glass™ haze filter. Recycles the haze as fluid, back to tank. No wasted fluid ever !
- Self-draining air filter, filter grade 5 microns only.
- Easy to read fluid level indicator.

Compressor unit features:

- New long-life Nexus™ piston industry standard compressor. MTBF 8,000+ hours.
- New air intercooler made with aluminium & copper.
- Compulsory fan cooling by a quiet high-speed fan, insures a normal working temperature during many hours of continuous operation.



THE MACHINE:

The all-new Ultimate 300 combines the superior haze quality from a cracker hazer with the quiet operation of an ordinary hazer. The compressor and haze units are able to separate, and by using an extension tube, the compressor is able to be hidden away for the ultimate in quiet operation.

THE HAZE:

Ultimate 300 has the same high output and unmatched performance of the Ultimate 200, and is suitable for theatre, concerts, festivals, corporate events or anytime where a clean, safe, dry, virtually invisible haze, and a silent operation is wanted.

EASY TO MAINTAIN:

Ultimate 300 is equipped with the unique EC 2 EasyClean feature, which facilitates easy and troublefree cleaning of the nozzle unit. Industrial super-rapid internal tube fittings insures quick and easy cleaning without the need of special tools. Internal tubes made with heat-resistant PUR (polurethane).

A new high-power air intercooler and a very effective air filter (filter grade 5 microns only) separates moisture from the compressed air. The air filter is equipped with automatic drain of condensed water, every time your machine is switched off!

The new main air filter cartridge is easy to replace in a second. Keep your hazer functioning like new for it's entire life !

OPTIONS:

Available in two versions, a base model with manual on / off, and a DMX model, with integrated DMX interface and manual override control.

2 years warranty (parts & labor).

FLUID:

Two kinds of fluid are available, Ultimate C-fluid for normal use, and Ultimate CXL fluid, which is special made for TV or theatre use, where an extremely light haze is wanted.

Models available:

- 30 200 - 240 Ultimate 300 Std. 240V 50Hz CE conform.
- 30 201 - 240 Ultimate 300 DMX 240V 50Hz CE conform.



Specifications:

Type:	“cracker” haze generator.
Fluid type:	Oil based, medical grade
Fluid consumption:	Approx. 0.06 ltr/hr continuous operation
Tank capacity:	Approx. 2.5 ltr, 40+ hrs runtime without refilling!
Operation:	Continuous
Warm-up time:	None (instant ON)
DMX interface (option):	Reads ch 1-255, uses one channel only.
Hazer dimensions:	W203 D405 H322 mm (incl. handle)
Compressor dim:	W203 D405 H297 mm (incl. handle)
As one unit dim:	W203 D405 H567 mm (incl. handle)
Weight: Hazer:	9,2 kgs, compr 14 kgs net
Power supply:	240V 50Hz 2,4 A
Pwr consumption:	240V: 580 Watts
Warranty:	2 years (parts & labor)



